



NOTES

1. All dimensions are in millimetres unless otherwise stated.
2. This drawing to be read in conjunction with all relevant architectural and other structural drawings.
3. Concrete to be class 20(20) mix 1:2:4 for reinforced concrete works.
4. Concrete for blinding to be class 15:1:3:6.
5. All excavations to be carried out to firm ground.
6. Cover to reinforcement to be as follows:
 Foundations 50mm
 Columns 40mm
 Beams 25mm
 Slab/staircase 20mm.
7. All timber to be sawn cypress of GS (structural grade of timber) cured to an optimum moisture content of 12-15% preservative treated.

ISSUES

DATE	TO	APPLICATION	BY

REVISIONS

NO	DATE	BY	DESCRIPTION	GRP LDR	C.S.ENG

REFERENCE DRAWINGS

NO	DESCRIPTION

CLIENT: **MINISTRY OF EDUCATION SCIENCE AND TECHNOLOGY**

PROJECT TITLE: **PROPOSED SUB COUNTY TECHNICAL TRAINING INSTITUTES**

DRG. TITLE: **FIRST FLOOR LAYOUT.**

Cl/sfb	()	
DRG. No.	TTI/STR/02	
FILE No.		

SCALE(S): AS SHOWN FIGURED DIMENSIONS ONLY TO BE TAKEN FROM THIS DRAWING

APPROVED

THE CHIEF ENGINEER(STRUCTURAL)

	NAME	SIGNATURE	DATE
DESIGNED	WATHOME A.M.		JUL 2015
DRAWN	WATHOME A.M.		JUL 2015

DIRECTORATE OF PUBLIC WORKS-UASIN GISHU COUNTY STRUCTURAL DEPARTMENT

